



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61C 7/14, 13/00	A1	(11) International Publication Number: WO 99/16380 (43) International Publication Date: 8 April 1999 (08.04.99)
(21) International Application Number: PCT/IL98/00451 (22) International Filing Date: 17 September 1998 (17.09.98) (30) Priority Data: 121872 30 September 1997 (30.09.97) IL (71) Applicant (for all designated States except US): CADENT LTD. [IL/IL]; Hamelacha Street 14, 60372 Or Yehuda (IL). (72) Inventors; and (75) Inventors/Applicants (for US only): TAUB, Eldad [IL/IL]; Topaz Street 11, 71908 Reut (IL). NISSENBAUM, Baruch [IL/IL]; Sara Haronson Street 23, 52293 Ramat Gan (IL). KOPELMAN, Avi [IL/IL]; Ido Street 8, 52233 Ramat-Chen (IL). (74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: PLACING AN ORTHODONTIC ELEMENT ON A TOOTH SURFACE		
(57) Abstract <p>A method, system and device for positioning and fixing an orthodontic element on a surface of a tooth are provided. The positioning of the element on a tooth is accomplished by: bringing the element into proximity of the tooth while continuously capturing an image of at least the tooth or of the element, and an image of both, once the tooth and the element are proximal to one another; transmitting the image or its representation to a display for displaying a real-life image of the captured image or representation together with indicators providing guidance information on intended position of the orthodontic element on the tooth's surface; positioning the element on a tooth's surface according to said indicators such that the element's position coincides with the intended position; and fixing the element onto the tooth.</p>		
<pre> graph TD 10 --> 12 12 --> 14 16 --> 14 14 --> 18 </pre>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PLACING AN ORTHODONTIC ELEMENT ON A TOOTH SURFACE

10 FIELD AND BACKGROUND OF THE INVENTION

The present invention is generally in the field of orthodontics and provides a method, system and device for placing an orthodontic element, e.g. a bracket on the surface of a tooth of an individual undergoing orthodontic treatment or for marking the spot on a tooth where such an element should be placed.

One of the most critical steps in an orthodontic treatment is the proper placement of brackets on surfaces of teeth of treated individuals. The location of the bracket on the tooth as well as its orientation is a critical factor in determining the direction of movement of the teeth during the treatment. In current orthodontic practice, the orthodontist decides on a general scheme of placing the brackets on the teeth and then attaches each of them to the surface of a tooth, in an exact location and orientation decided at the time of such placing. Preparatory to an orthodontic treatment, the orthodontist typically prepares a plaster model of the teeth of the treated individual and on the basis of such model, the general scheme of placement of the brackets can be decided. However, there is currently no available method which will allow to position the bracket correctly on a tooth surface, based on a determination made previously, e.g. based on a model.

In orthodontic treatment, the brackets are typically placed on the buccal surface of the teeth. At times, it is desired both from a treatment perspective as well as for reasons of external appearance of the individual, to place the brackets on the lingual surface of the teeth. However, by current
5 methods it is difficult to properly position the brackets on the lingual surfaces, particularly in view of difficulties in monitoring the position during attachment of the brackets.

GENERAL DESCRIPTION OF THE INVENTION

10 It is an object of the present invention to provide a method, system and device for positioning of an orthodontic element on a surface of a tooth, or for marking the position, where an element has to be subsequently placed. The positioning may be based on a prior determination of the proper position of the element on a tooth.

15 The term "*position*" is used herein to denote either the element's location on the surface of a tooth, its orientation or a combination of location and orientation. The term "*positioning*" will be used to denote the act of placing the bracket on the surface of a tooth in a desired position. The term "*element*" is used herein to denote a device, which is fixed on to a tooth within
20 the framework of an orthodontic treatment, e.g. a bracket.

In accordance with one aspect of the invention, there is provided a method for positioning and fixing an orthodontic element on a surface of a tooth, comprising:

- (a) bringing the element into proximity of the tooth while
25 continuously capturing an image of at least the tooth or of the element; and an image of both, once the tooth and the element are proximal to one another;
- (b) transmitting the image or its representation to a display for displaying a real-life image of the captured image or representation together

with indicators providing guidance information on intended position of the orthodontic element on the tooth's surface;

(c) positioning the element on a tooth's surface according to said indicators such that the element's position coincides with the intended
5 position; and

(d) fixing the element onto the tooth.

In accordance with another aspect of the invention there is provided a method for marking an intended position on a tooth where an orthodontic element is to be placed and fixed, the method comprising:

10 (a) providing a marking device with a marking member for making a visible mark on a tooth's surface;

(b) manipulating said device so as to bring said member into proximity of the tooth's surface while continuously capturing an image of at least the tooth or of the marking member, and of both once the tooth and the
15 marking member are proximal to one another;

(c) transmitting the image or a representation thereof to a display displaying said image or representation together with indicators providing guidance information on the intended position of the orthodontic element;

(d) fixing the position of the marking member on the tooth's
20 surface according to said indicators, such that the marking member's position coincides with the intended position of the orthodontic element; and

(e) applying a mark on the tooth's surface at said position.

The marking device may be a device adapted to attach a sticker to mark the position where the orthodontic element is to be fixed; adapted to
25 make a color mark on the tooth, e.g. by stamping, so as to mark said position; etc. The marked position of the element can then serve as guidance for replacement of an orthodontic element on the surface of a tooth.

In the following description the captured image or its representation which is displayed on the screen will be referred to at times as

"real-life image". As will be explained further below, coincidental with the real-life image, the display may also show a *"virtual image"* of the same object (the orthodontic element or one or more teeth) seen in the real-life image.

5 The indicators providing the guidance information on the screen may be represented in a number of ways. For example, the indicators may consist of a display of vectors defining the direction for a change of position or of a change of orientation needed in order to yield a position of the element on a surface of a tooth which was determined to be that which will yield
10 optimal results in the orthodontic treatment (such position will also be referred to herein at times as *"proper position"*). By another example, the guidance information may be provided in the form of a target sign, e.g. an "X" or a "+" marking the point of proper position of the orthodontic element superimposed on a display real-life image. By a further example, the guidance
15 information may be provided as a virtual image of objects corresponding to those of the real-life image, e.g. a graphic representation of boundaries of objects in the image (of the teeth or of the orthodontic element) which are presented such that once the real-life objects are made to overlap the responding object of the virtual image, proper position is attained. As will be
20 understood, the above are mere examples and a variety of other graphic representations providing guidance information may also be used.

 The real-life image and the guidance information are superimposed together on display. In order to yield a proper position of the orthodontic treatment, the element is moved or rotated, based on the guidance
25 information, until its real-life image displayed on the screen yields a correct position as determined on the basis of the indicators on the screen. For example, the proper position of an orthodontic bracket may be represented as a virtual image, e.g. boundaries of a bracket, superimposed on the real-life image of a tooth on which the bracket is to be fixed, and the bracket may then

be manipulated until the boundaries of its real-life image overlap those of the virtual image. Alternatively, the real-life image may be centered on the orthodontic element, e.g. the bracket, such that the orthodontic element is always in a fixed position on the screen. In such latter case, a virtual image of
5 at least one tooth may be displayed and the bracket may then be repositioned and/or rotated until the at least one tooth of the real-life image overlaps that of the virtual image, thus attaining the proper position.

By a further alternative, the displayed guidance information indicators, consist of a virtual image of both at least one tooth and of the
10 orthodontic element in a proper position of the latter. The user may then first be required to adjust the image capturing unit such that the displayed virtual image of the at least one tooth will overlap the corresponding at least one tooth of the real-life image, and then manipulate the orthodontic element until its position coincides with that of the virtual image.

15 The same above alternatives apply also, *mutatis mutandis*, in the case of the method defined above for making an intended position of an orthodontic element on a tooth.

A preferred embodiment of the invention, which will be illustrated in more detail below, concerns the case where the real-life image centers on the
20 orthodontic element or the marking member, in which case the real-life image thereof is continuously displayed in a fixed position of the display. A particularly preferred embodiment of the invention is such where the image capturing unit is mounted on the positioning device of the orthodontic element or of the marking member, thus having the orthodontic element or the
25 marking member (as the case may be) in a fixed position of its field of view. It should however be noted that it is possible also to achieve the same effect, namely displaying the real-life image of the orthodontic element on the display in a fixed position and orientation, by other means: for example, a stationary image capturing unit having the element in its field of view

captures the image of the orthodontic element or the marking member and then by various rapid (real-time) image processing algorithms the orthodontic element or the marking member may always appears in defined spot of the display. For this purpose the image processing software may identify the
5 element or the marking member by its contours, by its color or reflectiveness, by other clues, e.g. markings displayed thereon, etc.

The method according to this preferred embodiment for positioning and fixing an element on a surface of a tooth, comprises:

- (a) mounting the element on a positioning device;
- 10 (b) bringing the element into proximity of said surface while continuously monitoring the element by an image acquisition unit which captures an image of the element and its surroundings and transmits this image to a screen;
- (c) displaying on the screen
 - 15 (i) said image,
 - (ii) guidance information relating to a proper position of the element on said surface;
- (d) in case of discrepancy between actual position of said element, being the position of the element viewed on the screen, and said proper
20 position, correcting the actual position to match said proper position; and
- (e) fixing said element on said surface.

The method according to the preferred embodiment for marking a position on the surface of a tooth where an orthodontic element is to be subsequently positioned, the method comprising:

- 25 (a) a marking device, having a marking member for making a visible mark on a tooth;
- (b) bringing the marking member into proximity of said surface while continuously monitoring the marking member by an image acquisition

unit which captures an image of the marking member and its surrounding and transmits this image to a screen;

(c) displaying on the screen

(i) said image,

5 (ii) guidance information relating to a proper position of the element on said surface;

(d) in case of a discrepancy between actual position of said marking member, being the position viewed on the screen, and said proper position, correcting the actual position to match said proper position; and

10 (e) marking said position on said surface.

The invention also provides a method for comparing between an orthodontic element's actual position on the surface of a tooth and a proper position, the method comprising:

(a) monitoring the element, the tooth or both once the element and
15 the tooth are proximal to one another by an image acquisition unit which transmits an image to a screen that displays said image;

(b) displaying information on said screen regarding proper position of said element in a manner allowing to compare between the actual and the proper position.

20 The information on proper position of the element may, for example, be displayed in the form of a virtual image of the tooth on which the element is to be fixed, e.g. in the form of lines tracing the boundaries of the tooth. The virtual image may at times be displayed on the screen super-imposed on a displayed real image of the element or the marking
25 member and its surrounding, with the superimposition being such that when the element or the marking member is in its proper position on the tooth, the real image matches the virtual image. Additionally, said information may also be displayed in the form of lines tracing the boundaries of the tooth optionally together with lines tracing boundaries of neighboring teeth. The

orthodontist or the technician, which positions and fixes the element or the marking device on to the tooth, manipulates its position until such match is achieved.

Information regarding proper position may be obtained by a
5 variety of methods. For example, it may be obtained on the basis of a virtual three-dimensional computerized model of the teeth, which is then used for a computerized design of the proper position. From such a model a virtual image of the teeth, which is a frontal image at an angle in which the real image of the teeth will subsequently be captured by the image acquisition
10 unit, can then be generated. A three-dimensional virtual teeth model may be obtained, for example, in a manner described in PCT Application, Publication No. WO 97/03622 or that described in German Patent Application PCT Application, Publication No. WO 94/24957, the contents of which are being incorporated herein by reference. Additionally, an element's proper position
15 may also be obtained from a treatment scheme planned on the basis of a physical model, e.g. a three-dimensional plaster model. For example, brackets or mock-up brackets may be fixed on such a model within the framework of a treatment design, and then an image of a bracket on such a teeth model may be captured from an angle substantially the same as that of
20 the real image of the teeth which will be captured by the image acquisition unit.

The display screen may typically be a television screen, a computer display, an eyepiece display, (e.g. fixed to the frame attached to the orthodontist's head), and many others.

25 The present invention also provides a system for positioning an orthodontic element or a marking device having a marking member for marking a position for subsequent placement of an orthodontic element on a surface of a tooth, comprising:

- an image acquisition unit for capturing an image of the tooth or of said element, and an image of both once the tooth and said element are proximal to one another;

- an image grabber coupled to said image acquisition unit for
5 receiving the image captured by the image acquisition unit and transmitting an image or a representation thereof to a display unit; and

- a display unit, coupled to the image grabber, for displaying said image or representation.

The system of the invention preferably comprises also a
10 module, coupled to said display unit, for transmitting to the display unit data relating to guidance information relating to correct position of the orthodontic element on the tooth's surface, for display by said display unit in a superimposed position to the displayed real-life image or representation thereof. The guidance information will typically, but not exclusively, be displayed on
15 the screen as a representation of boundaries of either the orthodontic element or the teeth, which once matched with corresponding boundaries of the displayed real-life image or representation, will yield a proper position. Such a proper position display may for example be an indication, superimposed on the tooth's image, of the correct position of the orthodontic element.
20 Alternatively, such representation may consist of boundaries of teeth superimposed on an image of the orthodontic element (which is maintained in the image in a fixed position) and by moving the orthodontic element and matching the viewed image with the real-life image in a manner that teeth boundaries of both images coincide, correct positioning will be attained. The
25 same applies, *mutatis mutandis*, also for a placing of a member of a marking element.

By preferred embodiment of the above system, the image acquisition unit, typically a small video camera fitted with a lens allowing near focus and a wide field of view is mounted on the positioning device. In

such a positioning device the element or the marking device, as the case may be, is typically held in a fixed place, and the image acquisition unit is also fixed on said device such that the image of the element or marking device will always be in a defined place in the captured image.

5 The invention further provides a positioning device for positioning an orthodontic element on the surface of a tooth, comprising:

- a gripping member for holding said element and releasing it once it is fixed on the tooth surface; and
 - an image acquisition unit for capturing an image of the element
- 10 held on the gripping member and of its surrounding.

The invention still further provides a marking device for marking a position for subsequent placement of an orthodontic element on a surface of a tooth, comprising:

- a marking member held on said marking device in a manner
- 15 allowing to mark said position on a tooth surface; and
- an image acquisition unit for capturing an image of the marking device and of its surrounding.

The positioning device of the invention allows to position and fix orthodontic elements in a proper position even on surfaces, which are

20 difficult to view. A particular example is placing brackets on lingual surfaces of teeth.

The invention will now be illustrated below by some non-limiting specific embodiments, with references to the figures in the attached drawings. The illustrated embodiments refer to positioning of a

25 bracket, it being understood that the invention applies, *mutatis mutandis* also to positioning of other orthodontic elements.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the general design scheme of a system in accordance with the invention;

5 **Fig. 2** shows a bracket-positioning device in accordance with an embodiment of the invention;

Fig. 3 shows the device of **Fig. 2** during the process of positioning the bracket for fixing on a surface of a tooth (the teeth being schematically represented by rectangles), illustrating also the field of view of the camera;

10 **Fig. 4** shows the image, which is displayed on the screen, wherein:

Fig. 4A illustrates the real image captured by the video camera;

Fig. 4B illustrates a virtual image on the proper position of the bracket;

and

Fig. 4C illustrates a superimposition of the images of **Figs. 4A** and **4C**.

15 **Fig. 5** shows a real image as captured by the image acquisition unit camera superimposed with a virtual image displayed as lines of teeth boundaries, wherein:

Fig. 5A shows the bracket not in the proper position; and

20 **Fig. 5B** shows the bracket in its proper position with the teeth borders matching the contours of the virtual image;

Fig. 6 illustrates another embodiment of displaying information regarding the proper position, where rather than lines tracing the boundaries of teeth, displayed are reference lines defining the teeth boundaries;

25 **Fig. 7** shows an image similar to **Fig. 5** where in this case, rather than displaying a virtual image in the form of lines tracing the boundaries of the teeth, information on proper position is displayed in the manner illustrated in **Fig. 6**; and

Fig. 8 shows a marking device in accordance with an embodiment of the invention.

DESCRIPTION OF SPECIFIC EMBODIMENTS

Reference is first being made to Fig. 1 showing the general scheme of a system 10 in accordance with an embodiment of the invention.

5 An image 12 captured by an image acquisition unit is transmitted comprising the first unit 12 which comprises a camera to a processor 14 which also receives proper position information 16 and transmits both to display screen 16, e.g. a television screen, a computer monitor screen, etc. The image displayed on the screen may be captured by the image ("*real life image*") and
10 may be an image displaying the proper position information, or a superimposition of both one on the other.

A bracket-positioning device 20 in accordance with an embodiment of the invention is shown in Fig. 2. This device, of which only the front part is shown (the rear part where the device may be held by the orthodontist
15 is not shown) comprises bracket grippers 22, holding a bracket 24, a video camera 26, mounted on a mount 28 integral with bracket gripper 22. Bracket 24 may be fixed at a determined place in an exact position by means of a removable pin 29. It should be noted that rather than a video camera other image acquisition units may be used, e.g. a CCD device.

20 As can be seen in Fig. 3, the video camera 26 is positioned such and has a field of view, represented by a circle 30, allowing to view bracket 24 (typically at the center of the real life image), and tooth 33 on which the bracket is to be fixed, as well as at least a portion of the neighboring teeth 32 and 34. It is to be noted, that for proper positioning, the camera's
25 field of view should be wide enough to show boundaries of the tooth. This may be achieved either by insuring sufficient distance between bracket 24 and video camera 26 or alternatively by fitting camera 26 with a wide-angle lens.

Fig. 4A illustrates schematically a real life image as viewed by camera 26. Seen in Fig. 4A are tooth 33, portions of neighboring teeth 32 and

34 and bracket 24 at the center, held on a bracket gripper 22. A virtual image can be seen in Fig. 4B comprising contours of tooth 33' and a portion of neighboring teeth 32' and 34' corresponding to tooth 33 and teeth 32 and 34, respectively. The virtual image displays the image of the teeth, which will be
5 captured by the camera when the bracket will be in its proper position.

Superimposition of the two views can be seen in Fig. 4C. To attain a proper position, the bracket-positioning device has to be manipulated so as to cause the real image to tilt until matching the real life virtual images.

Fig. 5 shows a picture of an image as captured by a camera
10 mounted on the bracket positioning device, superimposed with a virtual image in the form of lines tracing the boundaries of the teeth. Fig. 5A shows a state where the bracket is in a position other than the proper position. By repositioning the bracket until the virtual image matches the boundaries of the teeth, a proper positioning of the bracket is attained.

15 Fig. 6 shows an alternative manner of displaying information regarding proper position. In this case, rather than displaying the boundaries of the teeth, reference lines 60, 62 and 64 are provided which define the extreme boundaries of the teeth. In addition, optionally, bracket positioning lines 66 and 68 may also be displayed to ensure that the bracket (represented
20 schematically by rectangle 69) is properly fitted on the bracket placer device; in a proper placement, bracket 69 will have its center on the crossing point between lines 66 and 68.

Fig. 7 shows the manner of obtaining proper positioning of a bracket in an analogous manner to that shown in Fig. 5 with Fig. 7A showing
25 a state in which the bracket is in a position other than the proper position and Fig. 7B shows the state after changing position to reach a proper position of the bracket with the reference lines serving as guidelines.

Fig. 8 shows a marking device 70 in accordance with an embodiment of the invention. Device 70 has a pair of gripping members 72

holding between them a marking member 74 fixed in position by means of pin 76. Device 70 further comprises a video camera 78, mounted on a mount 80 integral with members 72, being positioned and having a field of view such that it fuels marker member 74 essentially the center of its field of view.

- 5 Marking member 74 has the general shape representing that of a bracket and has a tooth engaging surface 82, which is capable of stamping a mark on a tooth which will thereafter serve as a guidance for proper positioning and subsequent fixing of a bracket. Positioning of member 74 thus to achieve a proper position may be carried out similarly as described above in reference to
- 10 Figs. 4-7.

CLAIMS:

1. A method for positioning and fixing an orthodontic element on a surface of a tooth, comprising:
 - 5 (a) bringing the element into proximity of the tooth while continuously capturing an image of at least the tooth or of the element; and an image of both, once the tooth and the element are proximal to one another;
 - (b) transmitting the image or its representation to a display for displaying a real-life image of the captured image or representation together
10 with indicators providing guidance information on intended position of the orthodontic element on the tooth's surface;
 - (c) positioning the element on a tooth's surface according to said indicators such that the element's position coincides with the intended position; and
15 (d) fixing the element onto the tooth.
2. A method according to Claim 1, wherein said markings comprise a virtual image of at least one tooth, the orthodontic element or both, and proper position is achieved by matching the real-life image with the virtual image.
- 20 3. A method according to Claim 2, wherein the virtual image consists of boundaries of the tooth, the orthodontic element or of both.
4. A method according to Claim 2 or 3, wherein the virtual image is a virtual image of the orthodontic element superimposed on said real-life image indicating the correct position and orientation of the orthodontic
25 element on a tooth's surface.
5. A method according to Claims 2 or 3, wherein
 - the virtual image is a virtual image of at least one tooth,
 - the image or representation of the orthodontic element is displayed at a fixed position and orientation of the display, and

- positioning the element on the tooth's surface is achieved by manipulating the element such that the at least one tooth of the image overlaps the at least one tooth of virtual image.

6. A method for positioning and fixing an orthodontic element on
5 a surface of a tooth, comprising:

- (a) mounting the element on a positioning device;
- (b) bringing the element into proximity of said surface while continuously monitoring the element by an image acquisition unit which captures an image of the element and its surrounding and transmits this image
10 to a screen;
- (c) displaying on the screen
 - (i) said image,
 - (ii) guidance information relating to a proper position of the element on said surface;
- 15 (d) in case of discrepancy between actual position of said element, being the position of the element viewed on the screen, and said proper position, correcting the actual position to match said proper position; and
- (e) fixing said element on said surface.

7. A method for comparing between an orthodontic element's
20 actual position on the surface of a tooth and a proper position, the method comprising:

- (a) monitoring the element, the tooth or both once the element and the tooth are proximal to one another by an image acquisition unit which transmits an image to a screen that displays said image;
- 25 (b) displaying information on said screen regarding proper position of said element in a manner allowing to compare between the actual and the proper position.

8. A method according to Claim 6 or 7 wherein the information regarding the proper position of the element comprises a virtual image of the tooth.

9. A method according to Claim 8, wherein the virtual image
5 comprises lines tracing boundaries of the tooth.

10. A method according to Claim 8 or 9, comprising superimposing the virtual image with a real image captured by the image acquisition unit displayed on the screen.

11. A method according to any one of Claims 1-3, wherein said
10 element is an orthodontic bracket.

12. A method according to any one of Claim 1-11, wherein the image acquisition unit is mounted on the positioning device.

13. A method according to Claim 12, wherein the element is held on by said device in a fixed, predetermined position.

14. A method according to Claim 13, wherein the position of the
15 element is such so that the element appears in the center of the image displayed on the screen.

15. A method for marking an intended position on a tooth where an orthodontic element is to be placed and fixed, the method comprising:

20 (a) providing a marking device with a marking member for making a visible mark on a tooth's surface;

(b) manipulating said device so as to bring said member into proximity of the tooth's surface while continuously capturing an image of at least the tooth or of the marking member, and of both once the tooth and the
25 marking member are proximal to one another;

(c) transmitting the image or a representation thereof to a display displaying said image or representation together with indicators providing guidance information on the intended position of the orthodontic element;

(d) fixing the position of the marking member on the tooth's surface according to said indicators, such that the marking member's position coincides with the intended position of the orthodontic element; and

(e) applying a mark on the tooth's surface at said position.

5 16. A method according to Claim 15, comprising:

(a) providing a marking device, having a marking member for making a visible mark on a tooth;

(b) bringing the marking member into proximity of said surface while continuously monitoring the marking member by an image acquisition
10 unit which captures an image of the marking member and its surrounding and transmits this image to a screen;

(c) displaying on the screen

(i) said image,

(ii) guidance information relating to a proper position of the
15 element on said surface;

(d) in case of a discrepancy between actual position of said marking member, being the position viewed on the screen, and said proper position, correcting the actual position to match said proper position; and

(e) marking said position on said surface.

20 17. A method according to Claim 16, wherein the information regarding the proper position of the element comprises a virtual image of the tooth.

18. A method according to Claim 17, wherein the virtual image comprises lines tracing boundaries of the tooth.

25 19. A method according to Claim 17 or 18, comprising superimposing the virtual image with a real image captured by the image acquisition unit displayed on the screen.

20. A system for positioning of an orthodontic element or a marking device having a marking member for marking a position for

subsequent placement of an orthodontic element on a surface of a tooth, comprising:

- an image acquisition unit for capturing an image of the tooth or of said element, and an image of both once the tooth and said element are proximal to one another;
- an image grabber coupled to said image acquisition unit for receiving the image captured by the image acquisition unit and transmitting an image or a representation thereof to a display unit; and
- a display unit, coupled to the image grabber, for displaying said image or representation.

21. A system according to Claim 20, comprising a module coupled to the display unit, for displaying markings providing guidance information on the tooth's surface, superimposed on said image or representation.

22. A system according to Claim 21, wherein said markings constitute of a virtual image of either at least one tooth, the orthodontic element or both.

23. A system according to Claim 22, wherein said virtual image comprises a boundary's representation.

24. A positioning device for positioning an element on the surface of a tooth, comprising:

- a gripping member for holding the element and releasing it once it is fixed on the tooth surface; and
- an image acquisition unit for capturing an image of the element held on the gripping member and of its surrounding.

25. A device according to Claim 24, wherein the element and the image acquisition unit are mutually fixed such that said element appears in a predetermined spot of the image captured by the image acquisition unit.

26. A marking device for marking a position for subsequent placement of an orthodontic element on a surface of a tooth, comprising:

- a marking member held on said marking device in a manner allowing to mark said position on a tooth surface; and
- an image acquisition unit for capturing an image of the marking device and of its surrounding.

5 27. A device according to Claim 26, wherein the marking member and the image acquisition unit are mutually fixed such that said member appears in a predetermined spot of the image captured by the image acquisition unit.

1/7






FIG.1

2/7



3/7




FIG. 4A




FIG. 4B




FIG. 4C

4/7




FIG. 5A




FIG. 5B

5/7




FIG. 6

6/7




FIG. 7A




FIG. 7B

7/7




FIG. 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL 98/00451

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 A61C7/14 A61C13/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 656 215 A (VIELFAURE GUY) 28 June 1991 see page 9, line 10-28 see page 10, line 15-33 see figures 2,3	1-3, 5-11, 15-27
A	----	4,12-14
A	WO 90 08512 A (DOLPHIN IMAGING SYSTEMS INC) 9 August 1990 see page 4, line 24-33 see page 5, line 24-30	1-27
A	US 4 850 864 A (DIAMOND MICHAEL K) 25 July 1989 see column 11, line 11-55 see figures 16,17 -----	1-27

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

12 January 1999

Date of mailing of the international search report

18/01/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Chabus, H

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 98/00451

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2656215 A	28-06-1991	FR 2655838 A	21-06-1991
WO 9008512 A	09-08-1990	US 5011405 A	30-04-1991
		AU 5097090 A	24-08-1990
		US RE35169 E	05-03-1996
US 4850864 A	25-07-1989	NONE	